



Software Information Sheet

JCM American Corporation TEL +1-702-651-0000
 JCM Germany GmbH TEL +49-211-530645-0
 JCM Gold (H.K.) Ltd. TEL +852-2429-7187
 JCM United Kingdom Ltd. TEL +44-870-770-2863
 Japan Cash Machine Co., Ltd. (Headquarters - Japan) TEL +81-6-6703-8405

General Information

Model Name:	DBV-30x-SU/SD				SW. Req. No. :			
SW. Name:	DBV-300(USA3)-SU ID-044				Date: (mm,dd,yyyy)	11.15.2005	Rev:	C1
SW. Version:	V1.31-24				Note:			
Country (Code):	United States of America (USA)				Guide:	Type1 (67mm)		
Currency:	Dollar				Check Sum:	82DE		
Direction:	4-Way				CRC (seed= 0000):	3173		
Denomination:	Denomi.	Printed	Issued	MRI#	Denomi.	Printed	Issued	MRI#
Years & MRI Ident #	\$1	'95 - '03	-	#443	\$50	'93 - '04	-	#447, #502, #516
	\$5	'93 - '03	-	#444, #449	\$100	'93 - '99	-	#448, #503
	\$10	'93 - '04	-	#445, #450	\$2	'95	-	#461
	\$20	'93 - '04	-	#446, #501, #515				
Barcode Ticket:	Not accepted.							
EPROM:	None							
Modifications:	<p>(Version 1.30-23 → 1.31-24)</p> <ul style="list-style-type: none"> Corrected Security Issue - Refer to OEM SIS for details. <p>(Version 1.28-20 → 1.30-23)</p> <ul style="list-style-type: none"> Corrected Security Issue - Refer to OEM SIS for details. <p>(DRAFT to V1.27-19)</p> <ul style="list-style-type: none"> Corrected Security Issue - Refer to OEM SIS for details. <p>(Version 1.13-04)</p> <ul style="list-style-type: none"> Corrected Security Issue - Refer to OEM SIS for details. 							
Memo:								

Dip Switch Settings

#	Dip Switch 1			Dip Switch 2	
1	OFF	\$1 ENABLE	OFF	Setting Pulse Width *1	RTS OFF: 5ms
	ON	\$1 DISABLE	ON		RTS OFF: 15ms
2	OFF	\$5 ENABLE	OFF	Setting Number of Pulse *2	Setting OFF
	ON	\$5 DISABLE	ON		Setting OFF
3	OFF	\$10 ENABLE	OFF	Setting OFF	Setting OFF
	ON	\$10 DISABLE	ON		Setting OFF
4	OFF	\$20 ENABLE	OFF	Setting OFF	Setting OFF
	ON	\$20 DISABLE	ON	Setting OFF	Setting OFF
5	OFF	\$50 ENABLE	OFF	Setting OFF	Setting OFF
	ON	\$50 DISABLE	ON	Setting OFF	Setting OFF
6	OFF	\$100 ENABLE	OFF	Setting OFF	Setting OFF
	ON	\$100 DISABLE	ON	Setting OFF	Setting OFF
7	OFF	\$2 ENABLE	OFF	Setting OFF	Setting OFF
	ON	\$2 DISABLE	ON	Setting OFF	Setting OFF
8	OFF	OFF	OFF	ON:PULSE I/F MODE	OFF:SERIAL I/F MODE
	ON	TEST MODE	ON	(ID-044)	(ID-044)

*1: Setting Pulse Width

SW1	SW2	Pulse Width
OFF	OFF	50ms/300ms
ON	OFF	50ms/50ms
OFF	ON	Not used
ON	ON	Not used

*2: Setting Number of Pulse

SW3	SW4	Number of Pulse
OFF	OFF	\$1 = 1 pulse
ON	OFF	\$1 = 2 pulse
OFF	ON	\$1 = 3 pulse
ON	ON	\$1 = 4 pulse

ID-044 Data Setting Specification

CREDIT DATA

CODE	Denomination
81h	\$1
82h	\$2
83h	\$5
84h	\$10
85h	\$20
86h	\$50
87h	\$100
88h	Reserved

SIGNAL DATA

CODE	Signal
89h	VEND
8Ah	RETURN
8Bh	REJECT
8Ch	ABN
8Dh	FULL